



Technical datasheet No.: **1681.7**

Product: VALMEX® Airtex® camp magic FR

Article No.: 7215 5946

Type of coating and finish			
Type of coating	PVC		
Finish	both sides lacquered (dull), fungicide		
Burning behaviour	California T 19, DIN 4102: B1, NFP 92507: M2 (Coloris blanc)		
for Burning behaviour	always check the validity of fire certificate		
Total weight	350 g/m ²	EN ISO 2286-2	
Tensile strength warp/weft	1200 / 1000 N/50 mm	EN ISO 1421/V1	
Tear strength warp/weft	130 / 80 N	DIN 53363	
Cold resistance	-20 °C	EN 1876-1	
High Temperature	+70 °C	PA 07.04 (intern)	
Translucence	15 %	at 550 nm	
Light fastness	>6 Note, Value	EN ISO 105 B02	
Crack resistance	no cracks	100000 x	DIN 53359 A
Base fabric			
Material	PES	ISO 2076	
Weave	L 1/1		
Remarks	preliminary datasheet		

These indicated technical data are based on average results. Due to production procedures deviations up to -5% can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.